

A versatile tool for fast testing of optical networks

OLT-20 Optical Loss Tester integrates laser source module and power meter module in one set, which can perform power testing and link loss testing in a optical fiber network conveniently. The typical applications include fiber identification, attenuation and loss measurement, continuity verification and fiber link transmission quality evaluation for installation, routine inspection and daily maintenance of MAN, WAN and CATV systems as well as for lab test and research work.

- ◆ Applicable on singlemode/multimode fibers
- ◆ Microprocessor & linear amplifier ensure long-time accuracy
- ◆ Quick response, no warm-up
- ◆ Interchangeable connectors: FC/SC/ST
- ◆ Dual-way power supply: 9V alkaline battery/AC adapter
- ◆ Pocketsize, large LCD display
- ◆ Multi-wavelength measurement
- ◆ Display units: dB/dBm/mW/ μ W
- ◆ Link loss testing
- ◆ CW/Modulation mode (270/1K/2K Hz)
- ◆ Low power indication/Auto off
- ◆ CE, FCC, FDA certificates



Specifications

Model	OLT-20			
	A	B	C	D
Laser Source Module				
Wavelength (± 20 nm)	1310/1550	850/1300	1310/1550	850/1300
Output Power	-7dBm			
Spectral Width	nm			
Emitter Type	FP-LD			
Stability	± 0.05 dB/15min ± 0.10 dB/8hr@1310/1550nm; ± 0.15 dB/8hr@850/1300nm			

MOD Frequencies	270, 1K, 2K Hz	
Connector Type	FC/PC (Interchangeable ST, SC)	
Optical Power Meter Module		
Detector Type	InGaAs	
Measurement Range	-70 ~ +10dBm ⁽¹⁾	-50 ~ +27dBm
Accuracy	± 5% ± 0.01nW (±0.5dB@850nm)	± 5%±1nW(±0.5dB@850nm)
Resolution	0.01dB	
Calibrated Wavelength ⁽²⁾	850, 1300, 1310,1490, 1550, 1625nm	
General Specifications		
Power Supply	9V Alkaline battery / optional 9V AC adapter	
Battery Life	OPM mode 40 hours; OPM+SLS mode 20 hours	
Operating Temperature	-20°C to 50°C	
Storage Temperature	-40°C to 70°C	
Relative Humidity	0 to 95% (Non-condensing)	
Weight	300g	
Dimension (HxWxT)	145x75x25mm	

Note: (1) At 850nm, the lower limit of measurement range is -60 dBm;
(2) Other wavelengths are open for customization.

* Specifications subject to change without notice

Ordering information

Standard Configuration:

Instrument, 9V alkaline battery, Rubber boot, Warranty card, CE certificate, Certificate of Calibration, User's manual

Optional Parts

Part Description	Part Number	Part Description	Part Number
3m, optical patch cord	AC-FJC-03-FC/FC	Ceramics core for LS	AC-FRL-C
SC connector for LS	AC-CONN-SC-L	SC connector for PM	AC-CONN-SC-P-300
ST connector for LS	AC-CONN-ST-L	ST connector for PM	AC-CONN-ST-P-300
AC adapter for US	AC-ADPT-10-US	Compact soft carry bag	AC-PB-10

